

Double Hung Windows

Region B:

N2	Wind Classification
400Pa	Serviceability
1000Pa	Ultimate Strength
150Pa	Water Penetration

STANDARD SIZES

Availability of standard sizes subject to wind load and water penetration requirements

Region C: Design wind pressure is calculated to 'AS/NZS 1170.2 Structural design actions – Wind action'

STUD	OPENING	660mm	960mm	1260mm	1560mm	1860mm	2160mm	2460mm	2760mm	3060mm
	FRAME SIZE	610mm	910mm	1210mm	1510mm	1810mm	2110mm	2410mm	2710mm	3010mm
950mm	900mm	 D0906	 D0909	 D0912	 DD0915	 DD0918	 DDD0921	 DDD0924	 DDD0927	 DDD0930
1050mm	1000mm	 D1006	 D1009	 D1012	 DD1015	 DD1018	 DDD1021	 DDD1024	 DDD1027	 DDD1030
1250mm	1200mm	 D1206	 D1209	 D1212	 DD1215	 DD1218	 DDD1221	 DDD1224	 DDD1227	 DDD1230
1550mm	1500mm	 D1506	 D1509	 DD1512	 DD1515	 DD1518	 DDD1521	 DDD1524	 DDD1527	 DDD1530
1850mm	1800mm	 D1806	 D1809	 DD1812	 DD1815	 DD1818	 DDD1821	 DDD1824	 DDD1827	
2150mm	2100mm	 D2106	 D2109	 DD2112	 DD2115	 DD2118	 DDD2121	 DDD2124	 DDD2127	

Note: Double Hung Windows may be subject to local variation or regulatory requirements