

C-View's  
sliding windows



For more information call C-View on  
**(07) 5520 1200**  
or visit [www.c-view.com.au](http://www.c-view.com.au)



# Residential range

## Key Features and Benefits

- Functional and easy-living design
- Clean finish and appearance thanks to concealed fixings
- Ideal in servery situations between kitchen and outside entertainment areas
- Wide frame makes cleaning a breeze – most vacuum heads fit easily inside the window track
- Integrated insect, safety and security screen options
- Optional vent locks allow the window to be secured while partially open for ventilation

**Note:** Features, benefits and performance parameters are subject to local variations, climate requirements and confirmation of structural performance

## Performance Parameters

<b>Frame size</b>	52mm
<b>Maximum window height</b>	1500mm (without low lites)
<b>Maximum window width</b>	3010mm
<b>Maximum panel width</b>	1500mm
<b>Maximum panel weight</b>	24kgs
<b>Maximum water rating</b>	600Pa
<b>Maximum wind rating</b>	4500Pa ULS
<b>Maximum glass thickness</b>	6.76mm (single glazed) 16mm (IGUs)
<b>Maximum acoustic rating</b>	Rw29
<b>Maximum bushfire attack level</b>	BAL 40





## Prestige range

### Key Features and Benefits

- Contemporary design suited for architecturally creative projects
- Clean finish and appearance thanks to concealed fixings and no visible sharp edges
- Ideal in servery situations between kitchen and outside entertainment areas
- Stylish handles are fitted with mortice lock for superior security
- High performance roller system ensures smooth sliding action at all times
- Integrated insect, safety and security screen options

### Performance Parameters

<b>Frame sizes</b>	67mm / 100mm
<b>Maximum window height</b>	2000mm (without low lites)
<b>Maximum window width</b>	5400mm
<b>Maximum panel width</b>	1350mm
<b>Maximum panel weight</b>	100kgs
<b>Maximum water rating</b>	600Pa
<b>Maximum wind rating</b>	6000Pa ULS
<b>Maximum glass thickness</b>	12.76mm (single glazed) 20mm (IGUs)
<b>Maximum acoustic rating</b>	Rw33
<b>Maximum bushfire attack level</b>	BAL 40