

# Sliding Doors

Region B:

N2	Wind Classification
400Pa	Serviceability
1000Pa	Ultimate Strength
150Pa	Water Penetration

## STANDARD SIZES

Availability of standard sizes subject to wind load and water penetration requirements

Region C: Design wind pressure is calculated to 'AS/NZS 1170.2 Structural design actions – Wind action'

		OPENING	1560mm	1860mm	2160mm	2460mm	2760mm	
		STUD	FRAME SIZE	1510mm	1810mm	2110mm	2410mm	2710mm
2130mm	2100mm							
			SF2115	SF2118	SF2121	SF2124	SF2127	
2430mm	2400mm							
			SF2415	SF2418	SF2421	SF2424	SF2427	

Also available in FS configuration

		OPENING	2288mm	2738mm	3188mm	3638mm	4058mm	
		STUD	FRAME SIZE	2238mm	2688mm	3138mm	3588mm	4038mm
2130mm	2100mm							
			FFS2122	FFS2127	FFS2131	FFS2136	FFS2140	
2430mm	2400mm							
			FFS2422	FFS2427	FFS2431	FFS2436	FFS2440	

		OPENING	3034mm	3634mm	4234mm	4834mm	5434mm	
		STUD	FRAME SIZE	2984mm	3584mm	4184mm	4784mm	5384mm
2130mm	2100mm							
			FSSF2130	FSSF2136	FSSF2142	FSSF2148	FSSF2154	
2430mm	2400mm							
			FSSF2430	FSSF2436	FSSF2442	FSSF2448	FSSF2454	

S = Sliding Panel  
F = Fixed Panel (Viewed from exterior)

**Note:** Sliding Doors may be subject to local variation or regulatory requirements